



SMA 30



SMA 40



SMA 50

- Mills Steel, Stainless Steel, Aluminum, Plastic or Wood
- Mills Contours and Cutouts Easily and Efficiently
- Mills Straight Bevel Widths up to 15 mm
- Mills Radius Edges of 2, 3, 4 or 6 mm
- Optional Clad Removal Adaptor Available

- Adjustable Depth Control
- Interchangeable Milling Heads between 10° & 80°
- Choice of 230V or 110V Motor
- Variable Speed Motor from 2500 – 7500 rpm
- No Chatter, No Vibration – Simple and Easy to Use

TOOL SPECIFICATIONS	UNIT	SMA 30			SMA 40			SMA 50		
Material (Stainless / Steel / Alum.)	-----	SS	S	AL	SS	S	AL	SS	S	AL
Max Bevel Width	mm	4	8	10	6	10	15	8	12	15
Radius dimension	mm	2 & 3 mm			2, 3 & 4 mm			2–15 mm		
Bevel angle	° (degree)	45 / 30 / 60			10 - 80			10 - 80		
Power	KW	1.2			1.2			1.8		
Spindle speed	RPM	2300 - 7000			2300 - 7000			2400 – 7300		
Weight	Kg	5.0			5.5			9.0		
Voltage Options	Voltage	110 / 230			110 / 230			110 / 230		
Inserts Set Choice	Qty Head	3			3, 4 or 5			3, 4 or 5		

See Videos of our Products at:
www.shmusa.com/products/beveling.htm